

Challenger Door

Bed Door Accessories Install

Date: 3/25/18

BY:AWY

****Be sure to check that Rough Opening measures to the size stated on the door label, and is square and even on all sides. Challenger Door sizes doors to properly fit whatever opening our customer has. Be sure that the opening has proper framework supporting it (ie; aluminum/steel tubing or lumber). For any clarification on how to measure Rough Opening visit <https://www.challengerdoor.com/measure/> ****

Tools and Supplies needed	<ul style="list-style-type: none">- screw gun- #10 screws $\frac{3}{4}$" long	
----------------------------------	---	---

Cable Installation

1. Fasten cable to Bracket with plastic bushing in position shown.
2. Open door until it is level with the ground
3. Prop or hold door open in a level position
4. Fasten cable brackets to sidewall of unit with a minimum # 10 screw size.
5. Check to make sure door is still level
6. Adjust bracket up or down as needed to make door level



1)



4)

Roof Bow Installation

1. Open door and lay tent bow in approximate position.
2. Measure 4" from top edge of door and 1.5" from side of door
3. Fasten bracket of tent bow with a #10 x 0.75" screw
4. Find center of opening and mark
5. Attach roof bow bracket as shown
6. Snap roof bow to tent bow
7. Insert into roof bow bracket to insure proper fit



2)



5)



7)

Tent Installation for tent with Slide on Hook

1. Open door
2. Slide tent into extrusion on door
3. Slide tent into extrusion on frame
4. Tap with soft mallet if necessary
5. Snap roof bow into tent bow
6. Push out to lift tent
7. Insert roof bow into bracket

2)



3)



4)



5)



6)



Tent Installation for Tent with Velcro

1. Open door
2. Lay tent onto door
3. Fasten Velcro on tent to Velcro on door by pressing firmly with thumb.
4. Slide tent into extrusion on frame
5. Tap with soft mallet if necessary
6. Snap roof bow into tent bow
7. Push out to lift tent
8. Insert roof bow into bracket

3)



4)



5)



6)



7)



8)

